

SHEET 1 SOUTH

Date: 09-23-2025 Author: DESIGNED BY CODY SOUTH REVIEWED & APPROVED BY TCS DEAN WALTMAN 956942 ATSSA

Comments:
TYPICAL ROAD CLOSURE & SIDEWALK CLOSURE W DETOUR ROUTE
CONTRACTOR: JIM W OKLAND
ALL TRAFFIC CONTROL EQUIPMENT SHALL MEET THE 2009 VERSION OF THE M.U.T.C.D
THATS RECONIZED BY ACHD AND ITD
ALL SIGNS SHALL BE BLACK ON ORANGE AND 48X48
THIS TRAFFIC CONTROL PLAN IS PROPERTY OF IDAHO EVENT SPECIALIST LLC
AND USE WITHOUT WRITTEN CONSENT IS PROHIBITED

Posted Speed: Mph
Sign Spacing: 0'
Shoulder Taper:
Merging Taper:
Shifting Taper:
Barrel Spacing:
Flagging Taper: 50' - 100' @ 20' Spacing
Downstream Taper: 50' - 100' @ 20' Spacing
Candlestick Tangent Spacing: ' Max
Delineator Spacing: '
Delineator Spacing On Corner's: 10'

Merging, Shifting and Shoulder Taper Lengths and Number of Channelization Devices (Cones) Used (not using flaggers)
(All minimums)

Lane Width	10 Feet				11 Feet				12 Feet				Shoulder Taper	
	L	W	S	D	L	W	S	D	L	W	S	D	Length	Devices
20	70	105	6	25	3	715	6	40	3	80	6	45	4	35
25	85	125	7	30	4	865	7	48	4	95	7	52	5	40
30	100	145	8	35	5	1015	8	56	5	110	8	60	6	45
35	115	165	9	40	6	1165	9	64	6	125	9	68	7	50
40	130	185	10	45	7	1315	10	72	7	140	10	76	8	55
45	145	205	11	50	8	1465	11	80	8	155	11	84	9	60
50	160	225	12	55	9	1615	12	88	9	170	12	92	10	65
55	175	245	13	60	10	1765	13	96	10	185	13	100	11	70
60	190	265	14	65	11	1915	14	104	11	200	14	108	12	75
65	205	285	15	70	12	2065	15	112	12	215	15	116	13	80
70	220	305	16	75	13	2215	16	120	13	230	16	124	14	85

Board Information:

- ① 7-Day Notification Boards.
To be placed Prior to Working.
- ② Work duration lasting longer than 3-Days:-
All Signs MUST be Post Mounted.
- ③ 1x Type III Barricade Per 10' lane MAY be placed completely across roadway or from curb to curb.
1x Beacon Light per Type III Barricades for Night Road Closure Protection.

Recommended Advanced Warning Sign Minimum Spacing

Road Type	Speed	Distance between Signs		
		A	B	C
Urban (Low Speed)	35 <	100 ft	100 ft	100 ft
Urban (High Speed)	35 >	350 ft	350 ft	350 ft
Rural	45	500 ft	500 ft	500 ft
Expressway/Freeway	60 +	1,000 ft	1,500 ft	2,640 ft

Reference: MUTCD
*Speed category to be determined by the State highway agency

ROAD TYPE	SPEED	DISTANCE BETWEEN SIGNS		
		A	B	C
URBAN (low speed)	35mph or lower	100FT	100FT	100FT
URBAN (high speed)	40 mph or greater	350ft	350ft	350ft
RURAL	30-55	500FT	500FT	500FT
EXPRESSWAY/FREWAY	55+	1000FT	1500FT	2640FT